


SPECIFICATIONS:

FUJITSU Document Scanner fi-7260



[Overview](#)
 [Features](#)
 [Accessories](#)
 [Specifications](#)
 [Warranty](#)
 [Support](#)

Model		fi-7260	
Functional Specifications			
Image Sensor Type		Color CCDs (Color Charge Coupled Device)	
Light Source		White LED Array	
Optical Resolution		600 dpi	
Output Resolution⁽¹⁾	Color (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments, 1200 dpi ⁽²⁾)	
	Grayscale (8 bit)		
	Monochrome		
Output Color Depth		Color: 24 bit, Grayscale: 8 bit, 4 bit; Monochrome: 1-bit	
Internal Video Processing		65536 levels (16 bit)	
Image Processing Function	Hardware	Deskew, cropping	
	Software	Multi-image, Blank page skip, i-DTC, Advanced-DTC, Simplified-DTC, sRGB, Auto color, Deskew cropping, Punch hole removal, Tab cropping, Upper lower separation, Error diffusion, Dither, Moire removal, Image Emphasis, Color cleanup, Dropout color (None, Specified, Color Saturation), Edge repair, Vertical Streaks Reduction	
Scanning Speed⁽³⁾ (A4, Portrait)	Color ⁽⁴⁾ Grayscale ⁽⁴⁾ Monochrome	ADF	Simplex: 60 ppm, Duplex: 120 ipm (200 dpi / 300 dpi)
	Color ⁽⁴⁾ Grayscale ⁽⁴⁾ Monochrome	Flatbed (fi-7260)	1.7 seconds (200 dpi)
ADF capacity⁽⁵⁾		80 Sheets (Letter 20 lb. or A4: 80 g/m2)	
Document	ADF minimum	2 x 2.13 in. (50.8 x 54 mm)	

size	ADF maximum ⁽⁶⁾	8.5 x 14 in. (216 x 355.6 mm)
	Long Document	8.27 x 220 in. (18.3') (210 x 5,588 mm) ⁽⁷⁾
	Flatbed (fi-7260)	8.5 x 11.69 in. (216 x 297 mm)
ADF Feeding Paper Weight (Thickness)	Letter	7.2 to 110 lb. (27 to 413 g/m ²)
	A8 sheets	34 to 56 lb. (127 to 209 g/m ²)
	Card ⁽⁸⁾	Up to 1.4 mm portrait and landscape feeding ⁽⁹⁾
Interface		USB 3.0 (backward compatible)
Minimum PC Specification		PaperStream IP i5 2.5 MHz Processor, 4 GB RAM
Physical Specifications		
Power requirements		100 to 240VAC ±10%
Power consumption		41 W or less Sleep: 1.8W; Standby: 0.35W ⁽¹⁰⁾
Dimensions (WxDxH) ⁽¹¹⁾		11.8 x 22.7 x 9.2 in. (300 x 577 x 234 mm)
Weight		19.4 lb. (8.8 kg)
Environmental Compatibility ⁽¹²⁾		ENERGY STAR® / RoHS / EPEAT Silver
Operating environment	Temperature	42° to 95°F (5° to 35°C)
	Relative humidity	20%-80% (non-condensing)
Inbox Contents		ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM, Getting Started Guide
Bundled Software		PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series, Scan to Microsoft SharePoint ⁽¹³⁾ , ABBYY FineReader for ScanSnap, Scanner Central Admin Agent
Options		Post-scan Imprinter (fi-7160 only), Carrier Sheet, Black Document Pad (fi-7260 only)
OS Support		Windows® 8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows XP® (32-bit/64-bit), Windows Server® 2008 (32-bit/64-bit), Windows Server® 2012 (64-bit)
Feed Detection Features		Ultrasonic Double Feed Detection Sensor, Acoustic Paper Protection Sensor, Intelligent Multi-Feed Function (Manual Bypass)
Other Features		Embossed Card Scanning Capability, Long Document Scanning, Scanner Central Admin management, USB 3.0 Support, Acoustic Paper Protection, Automatic: Color Recognition, Paper-Size Detection, De-skew Correction
Limited Warranty		One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.ImagingService.com or call (800) 301-9475.
Service Options		Post-Warranty - Advance Exchange Plus; restrictions apply. Consumables - ScanAid™ kits For full details, visit www.ImagingService.com or call (800) 626-4686.
Part Number		PA03670-B555